

CM

The CM cultivator series provides a variety of options inter-row plowing. Featuring special “Stone-Jumper” support system with anti-shock springs and adjustable width, these cultivators are ideal for working the soil in vineyards, orchards, and nurseries. Two inter-row heads can be combined to work the area near the plant on the same pass. Working depth is set by the rear roller between 6-10 inches.



MODEL	# of Blades	Work Width	Engine HP	Weight
CM 5/110	5	43"-61"	50-70	1036 lbs
CM 7/110	7	43"-61"	60-75	1168 lbs
CM 7/150	7	59"-77"	60-75	1213 lbs
CM 9/150	9	59"-77"	75-90	1411 lbs
CM 9/200	9	79"-96"	75-90	1455 lbs
CM 11/190	11	75"-93"	90-100	1653 lbs
CM 11/250	11	98"-116"	90-100	1698 lbs



FRM

The FRM disc harrow series features 24" cutting discs and also utilizes the “Stone-Jumper” anti-shock spring system. The frame has adjustable width and optional hydraulic lifting cylinders to tilt up the cultivator for transportation. The rear roller allows for working depths from 3-6 inches.



MODEL	# of Discs	Work Width	Engine HP	Weight
FRM 8D	8	47"-61"	50-70	1175 lbs
FRM 10D	10	59"-73"	55-75	1485 lbs
FRM 12D	12	63"-77"	60-75	1790 lbs
FRM 16D	16	78"-92.5"	75-90	1960 lbs
FRM 20D	20	98"-112"	90-100	2330 lbs