

The POWER HARROWS are the preferred tillage tool to work the soil deeply without turning layers of soil — top-soil stays on top. The machine can also be set for shallow cultivation. An optional rear roller can smash missed clods to leave a fine seedbed ready for seeding. Used in conjunction with spaders these tools can do all your mechanical tillage and soil cultivation in a manner that best preserves your soil life and structure.



**Alfa Series**

540 RPM Single Speed  
Gearbox Transmission  
260 RPM Rotor Speed

Adjustable 3 Point Hitch  
Cat. 1 Pin

Drive Shaft w/ Shear Bolt



**Sirio Series**

540 RPM Single Speed  
Gearbox Transmission  
260 RPM Rotor Speed

Adjustable 3 Point Hitch  
Cat. 1 and 2 Pins

Drive Shaft w/ Shear Bolt



**Beta Series**

540 RPM Single Speed  
Gearbox Transmission  
260 RPM Rotor Speed

Adjustable 3 Point Hitch  
Cat. 1 and 2 Pins

Drive Shaft w/ Shear Bolt



**Omega Series**

540/1000 RPM Speed  
Transmission  
193/236/288/353/357  
RPM Rotation Speed

Oscillating Hitch  
Cat. 2 Pins

Drive Shaft w/ Shear Bolt



**Gamma Series**

750/1000 3-Speed  
Transmission  
256/283/341/394 RPM  
Rotation Speed

Floating or Rigid Hitch  
Cat. 2 and 3 Pins

Drive Shaft w/ Shear Bolt



| Code        | Depth | Work Width | HP (min/max) | Rotors | # of Blades | Weight   |
|-------------|-------|------------|--------------|--------|-------------|----------|
| ALFA 110 R  | 8"    | 34"-35"    | 20/40        | 5      | 6 R + 4 L   | 540 lbs  |
| ALFA 130 R  | 8"    | 50"-51"    | 25/40        | 6      | 6 + 6       | 606 lbs  |
| ALFA 150 R  | 8"    | 58"-59"    | 30/40        | 7      | 8 R + 6 L   | 672 lbs  |
| SIRIO 150 R | 10"   | 58"-59"    | 30/70        | 7      | 8 R + 6 L   | 837 lbs  |
| SIRIO 170 R | 10"   | 66"-67"    | 35/70        | 8      | 8 + 8       | 892 lbs  |
| SIRIO 190 R | 10"   | 74"-75"    | 40/70        | 9      | 10 R + 8 L  | 959 lbs  |
| SIRIO 210 R | 10"   | 81"-83"    | 45/70        | 10     | 10 + 10     | 1025 lbs |
| BETA 205 R  | 11"   | 79"-81"    | 60/110       | 8      | 8 + 8       | 1497 lbs |
| BETA 230 R  | 11"   | 89"-90"    | 70/110       | 9      | 10 R + 8 L  | 1584 lbs |
| BETA 250 R  | 11"   | 98"-100"   | 80/110       | 10     | 10 + 10     | 1686 lbs |
| BETA 300 R  | 11"   | 116"-118"  | 90/110       | 12     | 12 + 12     | 1895 lbs |
| OMEGA 250 G | 11"   | 96"-99"    | 80/120       | 10     | 10 + 10     | 1962 lbs |
| OMEGA 300 G | 11"   | 115"-117"  | 90/120       | 12     | 12 + 12     | 2172 lbs |
| GAMMA 300 G | 12"   | 117"-120"  | 100/180      | 12     | 12 + 12     | 2921 lbs |
| GAMMA 350 G | 12"   | 141"-144"  | 130/180      | 14     | 14 + 14     | 3212 lbs |
| GAMMA 400 G | 12"   | 160"-163"  | 150/180      | 16     | 16 + 16     | 3432 lbs |

*R Models - Cage Roller/G Models - Packer Roller*